




Please read carefully before use and keep for future reference

1.PARTS IDENTIFICATION



1	Guard
2	Blade
3	Guard clip
4	Handle
5	Clutch handle
6	Motor
7	kneeJoint
8	Stand
9	Cord
10	Switch, LAMP
	,

2. HOW TO ASSEMBLE

- Turn the nut H counterclockwise and remove it.
- Place the rear guard in the proper position. Fit the protections into the guide holes of the guard.
- Tum the nut clockwise and tighten it completely.
- · Pull out tube of the shaft.
- Tighten the screw to fasten the blade.
- · Attach the front guard.

3.OPERATION

- The speed of the fan can be controlled by a digital indicating device, Pull the string the fan will start with "1" displayed. Further pulling-the string. the fan will speed up with the digital displaying "2" or "3" respectively, when the device displays "0" again, the fan stops.
- To change the direction of the air flow.push they
 edge of the guard to the desired position.
- The fan will start oscillating you push the handle, and stop oscillating push the handle

4. PAY PARTICULA RATTENTION TO THE FOLLOWING:

- 1.Use only with rated Voltage.
- 2.Do not use acids.chemicals oils.etc have been used.

5.GUIDE TO BETTER MAINTENANCE

- 1.Keep dry Never be of excessive humidity and water
- 2.Keep the fan clean. Wipe away dirt with a clean soft cloth, ordinary soap and water, wipe dry, Do not use solvents...etc. [gasoline or petroleum.]